IP65 NCC T5



- Energy Saving
- Polycarbonate Construction
- Stainless Steel clips
- Dimmable version available
- Integral Emergency option

T5 Non Corrosive luminaire, ideally suited to plant rooms, car parks and exposed communal areas where energy savings are looking to be achieved. Supplied with stainless steel clips and an all polycarbonate IP65 body with injected polyurethane gasket, suitable for mounting on conduit through wiring and suspending on chain or catenary wire.

ORDER CODES

1 x 14w	2ft 14w T5 Single	NCC114
1 x 24w	2ft 24w T5 Single	NCC124
1 x 28w	4ft 28w T5 Single	NCC128
1 x 54w	4ft 54w T5 Single	NCC154
1 x 35w	5ft 35w T5 Single	NCC135
1 x 49w	5ft 49w T5 Single	NCC149
1 x 80w	5ft 80w T5 Single	NCC180
2 x 14w	2ft 14w T5 Twin	NCC214
2 x 24w	2ft 24w T5 Twin	NCC224
2 x 28w	4ft 28w T5 Twin	NCC228
2 x 54w	4ft 54w T5 Twin	NCC254
2 x 35w	5ft 35w T5 Twin	NCC235
2 x 49w	5ft 49w T5 Twin	NCC249
2 x 80w	2ft 80w T5 Twin	NCC280
	With Integral Emergency	/EM
	With Integral LED Emergency	/EML
	With 1-10v Dimming	/DIM
	With DSI Dimming	/DIG
	With DALI Dimming	/DALI

SPECIFICATION

IP65 Polycarbonate Non-Corrosive with optional integral 3hr maintained emergency fitted, as Preslite NCC T5 Range.

