

8w Bulkhead



Specification

	Non Maintained	Maintained	Mains
Light Source	1 x 8 watt T5		
Construction	White Polcarb Body/ Clear Fresnel Lens		
Light Output Mains	N/a	100 lm	400 lm
Light Output Emergency	100 lm	100 lm	N/a
Battery	2.4 Volt 4Ah Nicad		
Charge Current	250mA Nominal		
Input Voltage	230 Volt AC +10% -6% 50 Hz		
Power	9 VA (Max)	21 VA (Max)	13 VA
Size	352mm x 108mm x 75mm		

A low cost IP65 rated bulkhead, designed to comply with EN 60598.2.22. Easy to install, this UK designed bulkhead is the ideal "simple" solution to basic emergency lighting. Available as 110 volt version for site applications.

SPECIFICATION

Emergency fluorescent luminaire constructed from polycarbonate body complete with clear fresnel lens. Supplied with lamp, as Preslite 8w Bulkhead Range.

ORDER CODES

Non Maintained	ZE1008NM
Maintained	ZE1018M
Non Maintained 110v	ZE1008NM/110
Maintained 110v	ZE1018M/110
Slave (24v/50v/110v)	ZE18/(24v/50v/110v)
Self Test	/ST
Adhesive Legend	ZE2L
Wire Cage	WCZE



Tel. +44 1204 575100
Fax. +44 1204 574100

email : sales@saturnlighting.co.uk
<http://www.saturnlighting.co.uk>