

Opaline



- Decorative surface mount 2D
- Energy efficient HF control gear
- Integral microwave sensor
- Auto dimming version available
- Integral Emergency option
- Opal TPa Diffuser

2D Luminaire for use in Toilets, Corridors, Stairwells and communal areas. Suitable for both wall and ceiling mounting. The body is powder coated spun aluminium, the diffuser is made from TPa Polycarbonate and is finished in an opal effect. Available in 325mm, 425mm & 525mm. Can be supplied with integral emergency and is also available with integral occupancy sensing microwave and integral auto-dimming occupancy sensing microwave.

ORDER CODES

16w	325mm 16w High Frequency	PLEOP316HF
28w	325mm 28w High Frequency	PLEOP328HF
16w	425mm 16w High Frequency	PLEOP416HF
28w	425mm 28w High Frequency	PLEOP428HF
38w	425mm 38w High Frequency	PLEOP438HF
16w	525mm 16w High Frequency	PLEOP516HF
28w	525mm 28w High Frequency	PLEOP528HF
38W	525mm 38w High Frequency	PLEOP538HF
	INTEGRAL LED EMERGENCY	/EML
	INTEGRAL MICROWAVE SENSOR	/CDDME
	INTEGRAL AUTODIM MICROWAVE SENSOR	/DIM/CDDME

SPECIFICATION

Spun Aluminium epoxy powder coated luminaire 325/425/525mm to take 2D lamp in 16/28/38w with provision for integral microwave motion detector and integral emergency, fitted with opal TPa diffuser retained by spring clips, as Preslite Opaline.