Opaline LED





- Energy Saving (12watts)
- Reduced Maintenance
- Dimmable version available
- Integral Emergency option
- Frosted Prismatic TPa Diffuser

ORDER CODES		
12w	325mm 12w	LDOP312
12w	325mm 12w c/w Microwave Sensor	LDOP312CDDME
12w	325mm 12w c/w Emergency	LDOP312EML
12w	325mm 12w c/w Microwave Sensor & Emergency	LDOP312/ CDDME/EML
12w	425mm 12w	LDOP412
12w	425mm 12w c/w Microwave Sensor	LDOP412CDDME
12w	425mm 12w c/w Emergency	LDOP412EML
12W	425mm 12w c/w Microwave Sensor & Emergency	LDOP412/ CDDME/EML

LED Luminaire for use in Toilets, Corridors, Stairwells and communal areas. Suitable for both wall and ceiling mounting. The body is white powder coated spun aluminium the diffuser is made from TPa Polycarbonate and is finished in a frosted prismatic effect. Available in both 325mm & 425mm. Can be supplied with integral emergency and is also available with integral occupancy sensing microwave and integral autodimming occupancy sensing microwave.

SPECIFICATION

Spun Aluminium epoxy powder coated luminaire fitted with thermally bonded LED chips and seperate driver with provision for integral microwave motion detector and integral emergency, fitted with frosted prismatic TPa diffuser retained by spring clips, as Preslite Opaline LED