

# LED Recessed Panel



- 42Watt
- 3100Lumen Output
- Typical 73Lm/W
- A Energy Rating
- 30,000hr LED's
- 2Year Warranty

## Technical Specification

|                        |          |
|------------------------|----------|
| Rated Input Voltage    | 220-240V |
| Input Voltage Range AC | 220-240V |
| Frequency              | 50/60Hz  |
| Power Factor           | 0.95     |
| Turn on time           | 0.5s     |

## Order Codes

|                                         |       |
|-----------------------------------------|-------|
| 3100Lm 42W LED Recessed Modular 600x600 | LDMFP |
| Remote 3hr Emergency                    | /EML  |
| DALI Dimmable                           | /DALI |

LED Luminaire for use in offices, reception areas, toilets, corridors & communal areas.

Suitable for both 15 & 25mm exposed tee ceiling mounting.

Integral thermal management of LED's with 3100Lm output.

The driver is a branded Philips LED Driver.

The housing is made from aluminium alloy, the diffuser is frosted PMMA. Low profile design requires less ceiling space.

Upto 50% energy saving compared to conventional recessed modular luminaires.

Easy installation and quick start. Can be supplied with remote emergency, suitable for use with externally mounted occupancy sensors.



Tel. +44 1204 575100  
Fax. +44 1204 574100

email : [sales@saturnlighting.co.uk](mailto:sales@saturnlighting.co.uk)  
<http://www.saturnlighting.co.uk>