

MSDC T5



- IP20 enclosed Steel body
- White powder coated steel body
- Framed TPb prismatic diffuser
- Dimmable versions available
- Integral Emergency Version

T5 Fluorescent surface luminaire for use in offices, reception areas, retail outlets and meeting halls. The body is white powder coated steel with a framed prismatic diffuser made from TPb styrene. Designed to be surface mounted. Available in 4x14W, 4x24W, 4x28W & 4x54W versions. Can be supplied with integral 3hr emergency, can be fitted with integral occupancy sensor and is also available in a dimmable version.

ORDER CODES

4 x 14W	2ft 4x14w cat2 surface modular	MSDC414
4 x 24W	2ft 4x24w cat2 surface modular	MSDC424
4 x 28W	4ft 4x28w cat2 surface modular	MSDC428
4 x 54W	4ft 4x54w cat2 surface modular	MSDC454
	1-10v dimming	/DIM
	DALI dimming	/DALI
	DSI dimming	/DSI
	3hr emergency	/EM
	occupancy sensor	/OCC

S P E C I F I C A T I O N

Rigid steel constructed fluorescent luminaire fully enclosed and powder coated in white finish c/w wishbone spring retained framed prismatic TPb styrene diffuser. Integral emergency, High Frequency digital or analogue dimming. Surface mounting. Supplied less lamp. As Preslite MSDC Range.